

Kestrel Evo Power Plus

Introducing the Kestrel S 5.7P Power Plus. This new model release of the Kestrel now takes this popular reach arm mower to a new level with increased power and additional features.

These features include integral road lighting, tubular 3 point linkage and power slew with hydraulic breakout.

Key Features

- 5.7m reach
- 60hp gear pumps
- Parallel arm standard
- Choice of flails, heads and cutter bars
- Power slew
- Steel hose covers standard



Want to know more about the Kestrel Evo Power Plus range?

Scan the QR code with a smart phone or tablet to instantly view the page.





Power slew and hydraulic breakout

For driver and machine safety.



Steel hose covers

Adding additional protection to drive motor houses.



Road lights & oil cooler

Fitted as standard.

Product Specification

● Standard ○ Optional — Not Available

Kestrel Evo Power Plus		5.7m (18'8")
Tractor requirements		
Minimum horse power		60hp
Minimum weight		3500kg 7716lbs
Base unit mounting options		
Front mount		○
Mid-mount		—
Rear mount		●
Three point linkage (Cat 11)		●
Axle bracket		—
Sub Frame		—
Yoke		—
Overall machine parameters		
Machine weight with head and oil		1210kg 2268lbs
Capacity of oil tank		160L 42.3usg
Weight of machine with oil but without head		970kg 2139lbs
Controls		
Cable Control (CC)		●
Low pressure hydraulics (LPH)		○
Electronic proportional control (EPP)		○
Intelligent control system (ICS)		●
Cable rotor reverse		—
Electronic rotor reverse		○
Hydraulic System		
System capability		60hp
Pump flow rate		100L 26.4usg
Pump type (Gear / Piston / Helical)		Gear
Pump arrangement (Twin / Tandem InLine)		Twin
Independent hydraulics		●
Oil cooler		○

Kestrel Evo Power Plus		5.7m (18'8")
Arm features and main frame		
Forward arm		—
Telescopic arm		—
Telescopic arm stroke		—
Power slew		●
Power slew angle		94°
Gravity breakout protection		—
Hydraulic breakout protection		●
Armfloat - manual operation		○
Armfloat - electronic operation		○
Head float - manual operation		●
Head float - electronic operation		●
Left hand cutting		○
Right hand cutting		○
Left and right hand cutting		—
Arm attachments available		
Variable track bracket (VTB)		○
Sheartrim cutter bar		○
Pro-Saw		○
Ditch cleaner		—
Rotary head		○
Accessories		
Road lights		●
Debris blower		○
Cab guard kit		●
Cutting heads (For Flail compatibility see 97)		
1.2m Pro-Trim with 115/150mm roller		●
1.2m Pro-Trim ISMP with 115/150mm roller		○



Parallel arm

Available as standard.

Working Reach

Head used for calcs: 1.2 Pro-Trim

Kestrel Evo Power Plus 5.7m (18'8")	
A	5.7m / 18'8"
B	5.9m / 19'4"
C	3.86m / 12'8"
D	5.1m / 16'9"
E	7.11m / 23'4"
X	1.3m / 4'1"
Y	1.0m / 3'4"

